



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

55744 ELECTRONIC LEAK DETECTOR FOR R744



SPECIFICATIONS:

- Operating Temperature: 32 - 122°F (0-50°C)
- Warm Up Time: 10 seconds
- Response Time: < 1 second
- Reset Time: < 1 second
- Sensitivity (High): < 400 ppm at 350 ppm ambient
- Sensitivity (Low): < 4,000 ppm at 350 ppm ambient
- Sensor Lifetime: > 2 years
- Probe Length: 12" (30cm)
- Batteries: 4 x 1/5V 'AA' Alkaline Batteries (6 VDC)
- Battery Life: 20 hours
- Dimensions: 8" x 2.5" x 2.25" (20.3 cm x 6.3 cm x 5.7 cm)
- Weight: 15 oz (425 grams) with batteries

Mastercool's Electronic Leak Detector for R744 is the most technologically advanced instrument of its kind. The minimal power requirements, small size and high sensitivity combine to create a tool which is easy to handle and ultra-effective at locating even the most difficult to find leaks.

