



**Mastercool<sup>®</sup> Inc.**  
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869  
PHONE: 973-252-9119 / FAX: 973-252-2455  
WEB: WWW.MASTERCOOL.COM

## ELECTRONIC CHARGING SCALE & CHARGING SOLENOID MODULE



### SPECIFICATIONS:

- 240 lbs (110Kg Capacity)
- Accuracy:
  - $\pm 0.16$  oz
  - $\pm 0.01$  lb
  - $\pm 0.01$  kgor 0.1% of reading (whichever is greater)
- Resolution: 0.02 lbs / 0.01 kg
- 3 hrs AUTO-OFF Function
- Operating Temperature: 32 to 120°F (0 to 49°C)
- Battery Life: Approx. 40 hrs
- 9" x 9" (22cm x 22cm) Platform

### 98210-A ACCU-CHARGE II ELECTRONIC CHARGING SCALE

**Charge Programming:** Allows user to program desired quantities. Before charge is complete, an alarm will sound allowing ample time to turn off refrigerant supply.

**Tank Capacity Programming:** Allows user to know the amount of refrigerant left in the tank at any time.

**Repeat:** Allows user to charge previously stored amount.



### 98230 CHARGING SOLENOID MODULE

This module allows the user to control the exact amount of refrigerant transferring to and from the A/C System. The compact design is battery powered (9V), lightweight, portable and works with all types of refrigerant. 98230 includes a short hose for tank connection, USB cord and 1/4"FL - 1/2"ACME adapters.