

## R12, R22, R502 ALUMINUM 2-WAY MANIFOLD



- Solid extruded aluminum body.
- Free-floating piston type valves reduce o-ring wear.
- Extra access port for vacuum line.
- Silicone dampened gauges smooth out needle movement.
- Gauges can be easily recalibrated in the field to maintain accuracy.
- Extra large sight glass for visual refrigerant check.
- Large easy-to-grip knobs.
- Models available for various types of refrigerants.

### [INSTRUCTIONS \(pdf\)](#)

R12, R22, and R502 2-way manifold gauge sets with hoses packaged in clamshells.  
Hose connections are 1/4" SAE. Gauges are 2 1/2" or 3 1/8" in PSI & °F.

HOSE LENGTH (SET OF 3) GAUGE SIZE	STANDARD HOSES STANDARD FITTINGS		STANDARD HOSES AUTO SHUT-OFF VALVES		NYLON BARRIER HOSES STANDARD FITTINGS		NYLON BARRIER HOSES AUTO SHUT-OFF VALVES		NYLON BARRIER HOSES MANUAL BALL VALVES	
	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"
36"	<b>93636</b>	<b>93136</b>	<b>95636</b>	<b>95536</b>	<b>96636</b>	<b>96136</b>	<b>97636</b>	<b>97136</b>	<b>92636</b>	<b>92136</b>
60"	<b>93661</b>	<b>93161</b>	<b>95661</b>	<b>95561</b>	<b>96661</b>	<b>96161</b>	<b>97661</b>	<b>97161</b>	<b>92661</b>	<b>92161</b>
72"	<b>93772</b>	<b>93172</b>	<b>95772</b>	<b>95572</b>	<b>96772</b>	<b>96172</b>	<b>97772</b>	<b>97172</b>	<b>92772</b>	<b>92172</b>

To order manifolds with shock-resistant gauge protectors, simply place a "-G" after the part number. (2 1/2" only)

#### **2-WAY MANIFOLD W/ GAUGES ONLY**

##### **93103**

R12, R22, R502 2 1/2" (1/4" FL-M)

##### **93113**

R12, R22, R502 3 1/8" (1/4" FL-M)

#### **PARTS FOR 2-WAY ALUMINUM MANIFOLDS**

##### **85215**

O-rings for Aluminum Manifolds (4 pcs)

##### **85216**

Seal & Seat Assembly (2 pcs)